

FIMIZOL EXPRESS

Primer based on bitumen and organic solvent

standard SRPS U.M3.240

PRODUCT DESCRIPTION:

FIMIZOL EXPRESS is a homogeneous mixture of bitumen and a special organic solvent which ensures short drying period thus fulfilling requirements of modern construction industry.

FIELDS OF APPLICATION:

FIMIZOL EXPRESS is applied as previous primer for preparation of waterproofing substrate, dust removal etc.

CHEMICAL COMPOSITION:

Primer based on bitumen and organic solvent

PRODUCT CHARACTERISTICS:

GENERAL FEATURES

Aspect		Liquid
Colour		Black
Bitumen content	%	min. 30
Softening point acc. to R&B	°C	min. 55
Point of inflammability acc. to Markuson	°C	max. 35
Flow resistance at elevated temperature, no leakage	°C	70
Flexibility at low temperature, no cracking	°C	4
Time of drying	min	60

USAGE:

It is used in cold condition, without dilution, well mixed before handling. It should be put with brush, roller or machine. The next work phase is done after drying of the painted mass. It must not be heated. Usage of open flame during work is PROHIBITED. When applied in closed areas good airing must be ensured. The average consumption is 0,35 kg/m², and varies from 0,2-0,5 kg/m².

PACKAGING, DELIVERY AND TRANSPORTATION:

FIMIZOL EXPRESS is delivered in packaging of 4, 5, 9, 23 and 180 kg. As highly inflammable material, it is stored and transported in covered areas and vehicles, protected from the sun, heat and mechanical damages.

Our products are made according to standard ISO 9001 and ISO 14001

